

# COMMANDER



<b>ROTAX® ENGINE</b>	<b>600R E-TEC</b>	<b>900 ACE</b>	<b>900 ACE Turbo</b>	<b>COLOUR</b>	Tactical Grey/Black
<b>Engine details</b>	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C.	Liquid-cooled, four-stroke D.O.H.C., turbo-charged	<b>DIMENSIONS</b>	
<b>Cylinders</b>	2	3	3	<b>Vehicle overall length*</b>	3240 mm
<b>Displacement</b>	599.4 cc	899.0 cc	899.0 cc	<b>Vehicle overall width</b>	1200 mm
<b>Bore</b>	72,3 mm	74 mm	74 mm	<b>Vehicle overall height</b>	1500 mm
<b>Stroke</b>	73 mm	69.7 mm	69.7 mm	<b>Ski stance</b>	996 mm
<b>Maximum engine speed</b>	8100 RPM	7250 RPM	7750 RPM	<b>Track nominal width</b>	500 mm
<b>Carburation</b>	Electronic Direct Injection	EFI	EFI	<b>Track nominal length</b>	3923 mm
<b>Recommended fuel type</b>	Unleaded	Unleaded	Unleaded	<b>Track profile height</b>	44 mm PowderMax
<b>Minimum octane</b>	95	95	95		
<b>Fuel tank</b>		42 liters			
<b>Oil tank capacity (2-stroke)</b>	3,4 liters				
<b>POWERTRAIN</b>				<b>SUSPENSION</b>	
<b>Gearbox</b>	2F/N/R with push-button reverse			<b>Front suspension</b>	LFS with bended lower A-Arms
<b>Drive clutch type</b>	pDrive with clickers (600R E-TEC) pDrive with slider shoes (900 ACE) pDrive (900 ACE Turbo)			<b>Front shock</b>	HPG 36
<b>Driven clutch type</b>	QRS			<b>Rear suspension</b>	EasyRide with adjustment
<b>Brake system</b>	Hydraulic brake with braided steel brake line, plastic master cylinder			<b>Center shock</b>	HPG 36
				<b>Rear shock</b>	HPG 36
<b>FEATURES</b>					
<b>Frame</b>	Radien-X			<b>Heated throttle lever</b>	Standard
<b>Skis</b>	Blade DS+			<b>Heated grips</b>	Standard
<b>Seating</b>	Modular, 1-up			<b>Gauge</b>	4.5-in. digital display
<b>Handlebar</b>	U-type steel with hooks, low grab handle			<b>Windshield</b>	Extra high with side deflectors
<b>Riser block height</b>	145 mm			<b>Hitch</b>	Standard
<b>Starter</b>	Electric			<b>Visor Plug front / rear</b>	Front
<b>Reverse</b>	RER (600R E-TEC) Electromechanical (ACE)			<b>USB power outlet</b>	Front
				<b>Air radiator with fan</b>	Yes
				<b>LinQ attachment</b>	Multi-LinQ plate

\* Vehicle overall length without snowflap.